

Галогенные лампы высоковольтные одноцокольные




Области применения


- Профессиональное кино- и телевизионное производство

Характеристики продукта


- Работа от сетевого напряжения: 120 В | 230 В | 240 В
- Цветовая температура: 2 900 К | 3 000 К (с увеличенным сроком службы)
- Цветовая температура: 3 200 К (для профессионального кино- и телепроизводства)
- Цветовая температура: 3 400 К (для обеспечения максимальной световой отдачи)




Данные о продуктовой линейке



358722_Halogen Lamp 64662



341357_HALOGEN STUDIO LAMP 64670



488277_HALOGEN LAMP 93591, 93592

Данные о продуктовой линейке

Technical data

Описание продукта	Информация о продукте	Электрические параметры	Фотометрические данные	Размеры и вес		
	Номер заказа	Номинальное напряжение	Цветовая температура	Диаметр	Длина	Освещаемое поле
64501 150 W 120 V	64501 150W 120V	120 В	3250 К	120 mm	550 mm	11,0*2,2 mm ²
64502 150 W 230 V	64502 150W GX6.	230 В	3200 К	180 mm	550 mm	13,0*1,9 mm ²
64502 150 W 240 V	64502 150W 240V	240 В	3200 К	1800 mm	550 mm	13,0*1,9 mm ²
64504 150 W 230 V	64504 A1/248 15	230 В	3200 К	1800 mm	620 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W GX6.	230 В	3200 К	185 mm	530 mm	9,6*12,5 mm ²
64505 200 W 230 V ¹⁾	64505 200W 240V	240 В	3200 К	185 mm	530 mm	9,5*12,5 mm ²
64512 300 W 120 V ¹⁾	64512 300W GX6.	120 В	3350 К	185 mm	530 mm	10,0*12,5 mm ²
64514 300 W 120 V ¹⁾	64514 300W GX6.	120 В	3200 К	185 mm	530 mm	10,0*12,5 mm ²
64515 300 W 230 V ¹⁾	64515 300W 230V	230 В	3300 К	185 mm	530 mm	9,8*12,5 mm ²
64515 300 W 240 V ¹⁾	64515 300W GX6.	240 В	3350 К	185 mm	530 mm	10,0*12,5 mm ²
64516 300 W 230 V ¹⁾	64516 300W GX6.	230 В	3150 К	185 mm	530 mm	9,8*12,5 mm ²
64516 300 W 240 V ¹⁾	64516 300W GX6.	240 В	3150 К	185 mm	530 mm	9,7*12,5 mm ²
64540 650 W 230 V	64540 BVM 650W	230 В	3400 К	240 mm	575 mm	14,0*15,0 mm ²
64540 650 W 240 V	64540 BVM 650W	240 В	3400 К	240 mm	575 mm	14,0*15,0 mm ²
64575 1000 W 230 V	64575 1000W 230	230 В	3400 К	240 mm	675 mm	14,0*14,0 mm ²
64575 1000 W 240 V	64575 1000W GX6	240 В	3400 К	240 mm	675 mm	14,0*14,0 mm ²
64748XS 1000W 240V	64748 XS 1000W	240 В	3200 К	2220 mm	950 mm	
64748XS 1000W 230V	64748 XS 1000W	230 В	3200 К	2220 mm	950 mm	
64662 300 W 230 V ²⁾	64662 300W GY9.	230 В	2900 К	150 mm	800 mm	9,0*11,0 mm ²
64672 500 W 230 V	64672 M40 500W	230 В	2900 К	220 mm	899 mm	12,0*11,0 mm ²

Данные о продуктовой линейке

	Информация о продукте	Электрические параметры	Фотометрические данные	Размеры и вес		
Описание продукта	Номер заказа	Номинальное напряжение	Цветовая температура	Диаметр	Длина	Освещаемое поле
64672 500 W 240 V	64672 M40 500W	240 В	2900 К	220 mm	899 mm	12,0*11,0 mm ²
64686 650 W 230 V	64686 DYR 650W	230 В	3200 К	210 mm	640 mm	10,0*10,0 mm ^{2 2)}
64686 650 W 240 V	64686 DYR 650W	240 В	3200 К	210 mm	640 mm	10,0*10,0 mm ^{2 2)}
93592 400 W 230 V ³⁾	93592 400W 230V	230 В	3200 К	200 mm	770 mm	10,7*12,2 mm ²
64662 300 W 240 V	64662 M38 300W	240 В	2900 К	1750 mm	800 mm	9,0*11,0 mm ²
64540 650 W 230 V	64540 650W GX6.	230 В	3400 К	2200 mm	575 mm	
64686 650 W 230 V	64686 650W GY9.	230 В	3200 К	2100 mm	640 mm	
64540 650 W 240 V	64540 650W GX6.	240 В	3400 К	2200 mm	575 mm	
64686 650 W 240 V	64686 650W 240V	240 В	3200 К	2100 mm	640 mm	

Описание продукта	Диаметр спирали	Срок службы	Дополнительные данные	Возможности / мощности	
		Срок службы	Цоколь	Положение горения	С регулировкой яркости
64501 150 W 120 V	2,2 mm	50 h	GX6.35	h90	
64502 150 W 230 V	1,9 mm	50 h	GX6.35	Любой	
64502 150 W 240 V		50 h	GX6.35	Любой	
64504 150 W 230 V		25 h	G6.35	s90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s90	
64505 200 W 230 V ¹⁾	12,5 mm	25 h	GX6.35	s90	
64512 300 W 120 V ¹⁾	12,5 mm	15 h	GX6.35	s90	
64514 300 W 120 V ¹⁾	12,5 mm	75 h	GX6.35	Other	
64515 300 W 230 V ¹⁾	12,5 mm	15 h	GX6.35	s90	
64515 300 W 240 V ¹⁾	12,5 mm	15 h	GX6.35	s90	
64516 300 W 230 V ¹⁾	12,5 mm	75 h	GX6.35	s90	
64516 300 W 240 V ¹⁾	12,5 mm	75 h	GX6.35	s90	
64540 650 W 230 V	15,0 mm	15 h	GX6.35	Любой	Да
64540 650 W 240 V	15,0 mm	15 h	GX6.35	Любой	
64575 1000 W 230 V	14,0 mm	15 h	GX6.35	s	
64575 1000 W 240 V	14,0 mm	15 h	GX6.35	s	
64748XS 1000W 240V			GY9.5	S180	
64748XS 1000W 230V			GY9.5	S180	

Данные о продуктовой линейке

Описание продукта	Диаметр спирали	Срок службы	Дополнительные данные	Возможности / мощности	
		Срок службы	Цоколь	Положение горения	С регулировкой яркости
64662 300 W 230 V ²⁾	11,0 mm	2000 h	GY9.5	Любой	
64672 500 W 230 V	11,0 mm	2000 h	GY9.5	Любой	
64672 500 W 240 V	11,0 mm	2000 h	GY9.5	Любой	
64686 650 W 230 V	10,0 mm	50 h	GY9.5	Любой	
64686 650 W 240 V	10,0 mm	50 h	GY9.5	Любой	
93592 400 W 230 V ³⁾	12,2 mm	75 h	GY9.5	s90	
64662 300 W 240 V	11,0 mm	2000 h	GY9.5	Любой	
64540 650 W 230 V			GX6.35	Other	
64686 650 W 230 V			GY9.5	Любой	
64540 650 W 240 V			GX6.35	Other	
64686 650 W 240 V			GY9.5	Other	

Описание продукта	Классификация		Условия поставки	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	ANSI код	Малое усилие подключения	EAN 10 of contained light source	Date of Declaration
64501 150 W 120 V	Other		4008321746030	25-04-2024
64502 150 W 230 V	Other		4052899080751	25-04-2024
64502 150 W 240 V	Other		4052899363236	25-04-2024
64504 150 W 230 V	Other	A1/249	4052899101654	06-03-2024
64505 200 W 230 V ¹⁾	Other		4008321746078	25-04-2024
64505 200 W 230 V ¹⁾	Other		4008321746092	25-04-2024
64512 300 W 120 V ¹⁾	Other		4008321746115	25-04-2024
64514 300 W 120 V ¹⁾	Other	CP/96	4008321746139	25-04-2024
64515 300 W 230 V ¹⁾	Other		4008321746153	25-04-2024
64515 300 W 240 V ¹⁾	Other		4008321746177	25-04-2024
64516 300 W 230 V ¹⁾	Other	CP/97	4008321746191	25-04-2024
64516 300 W 240 V ¹⁾	Other	CP/97	4008321746214	25-04-2024
64540 650 W 230 V	BVM		4052899158221	25-04-2024
64540 650 W 240 V	BVM		4052899158245	25-04-2024
64575 1000 W 230 V	EGY		4052899274556	25-04-2024
64575 1000 W 240 V	EGY		4052899274570	25-04-2024
64748XS 1000W 240V			4052899545380	22-04-2024
64748XS 1000W 230V			4052899545366	22-04-2024
64662 300 W 230 V ²⁾	Other		4052899015449	22-04-2024
64672 500 W 230 V	Other		4008321098559	22-04-2024
64672 500 W 240 V	Other		4008321098535	22-04-2024
64686 650 W 230 V	Other		4052899158269	05-03-2024
64686 650 W 240 V	Other		4052899158283	05-03-2024

Данные о продуктовой линейке

	Классификация		Условия поставки	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Описание продукта	ANSI код	Малое усилие подключения	EAN 10 of contained light source	Date of Declaration
93592 400 W 230 V ³⁾	Other		4050300481531	05-03-2024
64662 300 W 240 V	Other	M/38	4052899144248	22-04-2024
64540 650 W 230 V	Other			06-03-2024
64686 650 W 230 V	Other			06-03-2024
64540 650 W 240 V	Other			06-03-2024
64686 650 W 240 V	Other			06-03-2024

Описание продукта	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64501 150 W 120 V	4050300279237 4008321746030	No declarable substances contained	In work
64502 150 W 230 V	4008321133335 4008321746054 4052899080751	No declarable substances contained	No declarable substances contained
64502 150 W 240 V	4052899080775 4052899363236	No declarable substances contained	In work
64504 150 W 230 V	4052899101654	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098436 4008321173881 4008321746078	No declarable substances contained	No declarable substances contained
64505 200 W 230 V ¹⁾	4008321098610 4008321746092	No declarable substances contained	No declarable substances contained
64512 300 W 120 V ¹⁾	4008321098634 4008321746115	No declarable substances contained	No declarable substances contained
64514 300 W 120 V ¹⁾	4008321098672 4008321746139	No declarable substances contained	No declarable substances contained
64515 300 W 230 V ¹⁾	4008321098696 4008321746153	No declarable substances contained	No declarable substances contained
64515 300 W 240 V ¹⁾	4008321189110 4008321746177	No declarable substances contained	No declarable substances contained
64516 300 W 230 V ¹⁾	4008321098733 4008321746191	No declarable substances contained	No declarable substances contained
64516 300 W 240 V ¹⁾	4008321098757 4008321746214	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4052899158221	No declarable substances contained	No declarable substances contained
64540 650 W 240 V	4052899158245	No declarable substances contained	No declarable substances contained
64575 1000 W 230 V	4008321098856 4052899274556	No declarable substances contained	No declarable substances contained

Данные о продуктовой линейке

Описание продукта	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
64575 1000 W 240 V	4008321087775 4008321098450 4052899274570	No declarable substances contained	No declarable substances contained
64748XS 1000W 240V	4052899545380	No declarable substances contained	No declarable substances contained
64748XS 1000W 230V	4052899545366	No declarable substances contained	No declarable substances contained
64662 300 W 230 V ²⁾	4008321097873 4052899015449	No declarable substances contained	No declarable substances contained
64672 500 W 230 V	4008321098559	No declarable substances contained	No declarable substances contained
64672 500 W 240 V	4008321098535	No declarable substances contained	No declarable substances contained
64686 650 W 230 V	4052899158269	No declarable substances contained	No declarable substances contained
64686 650 W 240 V	4052899158283	No declarable substances contained	No declarable substances contained
93592 400 W 230 V ³⁾	4050300481531	No declarable substances contained	No declarable substances contained
64662 300 W 240 V	4052899144248	No declarable substances contained	No declarable substances contained
64540 650 W 230 V	4008321098818		In work
64686 650 W 230 V	4008321098498 4008321133359		In work
64540 650 W 240 V	4008321098795		In work
64686 650 W 240 V	4008321098511		In work

1) По технологии штампованной кварцевой лопатки

2) С моноспиралью

3) По запросу

Данные о продуктовой линейке

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Ссылки

Дополнительную информацию по пинч-технологии см. в следующей брошюре:

“A whole lotta shakin’ goin’ on!” («Настоящая встряска!») Новые галогенные лампы с пинч-технологией, используемой в кварцевых лампах. (122 Вт 100 DE 08/05)

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.