Product family datasheet

OSRAM

DIADEM CHROME

Only amber during operation



Chrome design Thanks to cutting edge interference and

absorber coating

Amber when ON ence and Only amber when operating, otherwise almost invisible

Homogenous appearance

Reflector has a fully homogenous chrome look





The design light with chrome look

OSRAM DIADEM CHROME signal lamps have a strikingly exclusive design: their chrome look made possible by a cutting edge interference and absorber coating. The lamps emit amber light only when operational. At other times, they are almost invisible and have no irritating color effects. DIADEM CHROME lamps are ideal for all indicator lights with clear covers.

Product family datasheet

Technical data

	Product information		Electrical	Photom etrical data			
Product description	Order reference	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminou s flux
DIADEM CHROME PY21W	7507DC	Auxiliary lamp	25 W	12.0 V	21.00 W	13.5 V	280 lm
DIADEM CHROME WY5W ¹⁾	2827DC	Auxiliary lamp	5 W	12.0 V	5.00 W	13.5 V	30 lm

		Dimensions & weight	Lifespan		Capabilities	Certificates & standards
Product description	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Technology	ECE category
DIADEM CHROME PY21W	±20 %	25.0 mm	100 h	250 h	AUX	PY21W
DIADEM CHROME WY5W ¹⁾	±20 %	10.0 mm	200 h	500 h	AUX	WY5W

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)						
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database			
DIADEM CHROME PY21W	05-03-2024	4008321972774 4052899241657 4052899417977 4052899418011 4062172211529 4062172271950 4052899979918 4062172394857	No declarable substances contained	In work			
DIADEM CHROME WY5W ¹⁾	05-03-2024	4008321972750 4052899067790 4052899417915 4052899417953 4052899417939 4052899979925 4062172394758	No declarable substances contained	In work			

¹⁾ Amber lamp for clear indicators

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





0'0



