

## LEDDriving PX-5

LED daytime running light for retrofit



### LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology



### DRL

LED daytime running light compatible with a wide range of car models and easy to install



### 5200 K

For drivers who want to increase visibility during the day



### Stylish highlights for your car

LEDDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

## Product family datasheet

### Technical data




Product description	Electrical Data		Photometric Data	
	Nominal voltage	Nominal wattage	Color temperature	Nominal luminous flux
LEDriving PX-5	12 V	12 W	5200 K	300 lm
LEDriving PX-5	12 V	12 W	5200 K	550 lm

Product description	Physical Attributes & Dimensions	Additional product data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Length	Connector to lamp	Candidate list substance 1	CAS No. of substance 1
LEDriving PX-5	160.0 mm	Wire Kit	Lead	7439-92-1
LEDriving PX-5	160.0 mm	Wire Kit	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving PX-5	The identification of the Candidate List substance is sufficient to allow safe use of the article.	24fd4b7d-c774-46f3-9b44-7c1767b813ea
LEDriving PX-5	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7a05b6d4-2aed-41c9-afdf-7da8dfd39471

## Product family datasheet

### Download Data

File	
	User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual)
	User instruction LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)
	User instruction GPRS_Safety symbols instructions

#### Legal advice

ECE E4 approval ECE R87 approval

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

