

Product family datasheet

LEDriving PX-5

LED daytime running light for retrofit



LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology



DRL

LED daytime running light compatible with a wide range of car models and easy to install



5200 K

For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Product family datasheet

Technical data

Product description	Electrical Data		Photometric Data	
	Nominal voltage	Nominal wattage	Color temperature	Nominal luminous flux
LEDriving PX-5	12 V	12 W	5200 K	300 lm
LEDriving PX-5	12 V	12 W	5200 K	550 lm

Product description	Physical Attributes & Dimensions	Additional product data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Length	Connector to lamp	Candidate List Substance 1	CAS No. of substance 1
LEDriving PX-5	160.0 mm	Wire Kit	Lead	7439-92-1
LEDriving PX-5	160.0 mm	Wire Kit	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDriving PX-5	The identification of the Candidate List substance is sufficient to allow safe use of the article.	24fd4b7d-c774-46f3-9b44-7c1767b813ea
LEDriving PX-5	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7a05b6d4-2aed-41c9-afdf-7da8dfd39471

Product family datasheet

Download Data

File
 User instruction LED Daytime Running Light Kit LEDDRL301 (User Manual)
 User instruction LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)
 User instruction GPRS_Safety symbols instructions

Соответствие стандартам

ECE E4 approval

ECE R87 approval

Ссылки

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

