

# LEDriving PREMIUM SL P21/5W

Ideal replacement for any vehicle





Wide range of different light colors

Available in Cool White, Amber and Red for a variety of customization options



Excellent homogeneity

Non-selective illumination thanks to modern diffuser material



Matches P21/5W lamps

Upgrade to LED with simple plug & play replacement



# Suitable LED replacement for P21/5W

LEDriving PREMIUM PY21/5W replacement lamps are compatible with conventional P21/5W lamp bases. The retrofit lamps are available in three different light colors for various applications (Cool White, Amber and Red) and offer an easy plug & play replacement, regardless of base polarity. OSRAM offers a 6 year guarantee for these LEDriving PREMIUM lamps. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

# Technical data

	Electrical	Data	Photometric Data		
Product description	Power input	Nominal voltage [calc.]	Nominal wattage [calc.]	Test voltage	Nominal luminous flux [calc.]
LEDriving PREMIUM SL	1.56 / 0.594 W	12 V	2 W	13.5 V	144/26 lm
LEDriving PREMIUM SL	1.65 / 0.44 W	12 V	2 W	13.5 V	38/5 lm
LEDriving PREMIUM SL	1.54 / 0.44 W	12 V	2 W	13.5 V	82/6.6 lm

		Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Luminous flux tolerance	Diameter [calc.]	Lifespan B3	Lifespan Tc	Primary Article Identifier
LEDriving PREMIUM SL	±25 %	25.7 mm	2500 hr	5000 hr	4052899321960   4052899433878   4052899433854
LEDriving PREMIUM SL ≜ P21/5W	±20 / ±25 %	25.7 mm	2500 hr	5000 hr	4052899433991   4052899433977   4052899322004
LEDriving PREMIUM SL ≜ P21/5W	±20 / ±25 %	25.7 mm	2500 hr	5000 hr	4052899433939   4052899433915   4052899321984

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDriving PREMIUM SL ≜ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9b21bd6f-9e67- 4928-bac8- d9da2d94ad5a   4c75e56c-d159-44cf- 92b1-5b3ef2e416ba   7f5e495d-a055- 4a12-ae43- ba11ea822892
LEDriving PREMIUM SL ≜ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	13874937-4192- 4f27-8c80- 879ae9c431e2   7d3b177a-fc02- 433e-8f03- b9c5b779cee0   1c4a29c8-89c2- 414c-955f- d590a749752f

Product description	Candidate List Substance 1	CAS No. of substance	Safe Use Instruction	Declaration No. in SCIP database
LEDriving PREMIUM SL ≙ P21/5W	Lead	7439-92-1	The identification of	55d082b4-b792-
			the Candidate List	4057-a8ae-
			substance is	907af0305b5c
			sufficient to allow	7736a687-a01d-
			safe use of the	4347-92db-
			article.	903136371f8e
				696dbb1c-125d-
				4633-a476-
				7c846a749a5c

#### Download Data

	File
<b>Z</b>	User instruction GPRS_Safety symbols instructions
太	Brochures LEDriving Retrofits - Exchange overview (EN)
乙	Brochures Sales Folder LEDriving replacement lamps (EN)
	ref_pim_amsp_product360degreeimages LEDriving PREMIUM Retrofit 1557CW
	ref_pim_amsp_product360degreeimages NIGHT BREAKER H7-LED 64210DWNB
	ref_pim_amsp_product360degreeimages LEDriving PREMIUM Retrofit 1557YE-02B

#### Соответствие стандартам

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

#### Ссылки

Guarantee terms are available at www.osram.com/am-guarantee

### **Application advice**

For more detailed application information and graphics please see product datasheet.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















