

LEDDriving SL P27/7W

Ideal replacement for any vehicle



Different light colors for various applications

Available in Cool White, Amber and Red



High brightness

High light intensity thanks to powerful LEDs and solid thermal management



Matches P27/7W lamps

Upgrade to LED with simple plug & play replacement



Suitable LED replacement for P27/7W

The LEDDriving STANDARD retrofit lamps for P27/7W offer an easy plug & play replacement. The lamps are shock- and vibration-proof and almost maintenance-free thanks to their long lifetime. Discover the different application possibilities with the exterior LED lamps. OSRAM provides a 4 year guarantee for this product. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage [calc.]	Nominal wattage [calc.]	Test voltage	Nominal luminous flux [calc.]
LEDDriving SL \triangleq P27/7W	2.75 W	12 V	2 W	13.5 V	150/45 lm
LEDDriving SL \triangleq P27/7W	1.10 W	12 V	1 W	13.5 V	13/6 lm
LEDDriving SL \triangleq P27/7W	3.30 W	12 V	3 W	13.5 V	30/10 lm




Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter [calc.]	Lifespan B3	Lifespan Tc	Primary Article Identifier
LEDDriving SL \triangleq P27/7W	$\pm 20\%$	25.0 mm	1500 hr	4000 hr	4052899435148 4052899435124 4052899330023 4052899385702
LEDDriving SL \triangleq P27/7W	$\pm 20\%$	25.0 mm	1500 hr	4000 hr	4052899435247 4052899330528 4052899435223
LEDDriving SL \triangleq P27/7W	$\pm 20\%$	25.0 mm	1500 hr	4000 hr	4052899435179 4052899385726 4052899435193 4052899330566

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving SL \triangleq P27/7W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e96292bc-e872-4051-9d31-570ecdb367f6 2c60d674-c456-4498-96c6-3ffe061809eb d8d81dac-e9a5-4a9a-90f2-81c8ef86a693 99fb7aa9-2b05-4191-84ac-510a9b61bf9f
LEDDriving SL \triangleq P27/7W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	53f8f8d8-fcdd-4788-94ab-74d396a2f8b1 9c67f773-8761-4c1d-b0d6-fd1e75efec00 ed34b883-afa6-439b-9296-883ea09039a9

Product family datasheet

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving SL ≙ P27/7W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d3bd713d-382e-43f1-9897-49d39b757bba ce562ab7-dbdb-46ec-9a49-291428b61c2a a1f88b2c-216c-4261-bb6d-7759fed9bf30 62c84433-f851-49ad-af44-894dceeadb32

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)
	Brochures Sales Folder LEDriving replacement lamps (EN)

Соответствие стандартам

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Ссылки

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

