



Области применения

- Concert Lighting
- Club & Disco
- Architecture & Architainment

CBP_09.00 Product features and benefits, all [calc.]

- Proven, reliable technology for entertainment and architectural fixtures
- Designed with an outer quartz jacket providing compact and rugged construction
- High luminous efficacy of up to 90 lumens/watt



 CONTAINS
MERCURY

Product family datasheet

Technical data

Product description	Electrical Data			Photometric Data Color temperature
	Nominal wattage	Nominal voltage	Nominal current	
HSR 400 W/60	400 W	67 V	6.9 A	6000 K
HSR 575 W/60	575 W	95 V	7 A	6000 K
HSR 575 W/72	575 W	95 V	7 A	7200 K

Product description	Physical Attributes & Dimensions	Lifetime Data
	Lamp base	Average Rated Life [GMS]
HSR 400 W/60	GX9.5	1000 hr
HSR 575 W/60	GX9.5	1000 hr
HSR 575 W/72	GX9.5	1000 hr

Product family datasheet

Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure during operation, HSR lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.