

6.6 A Current Controlled Halogen - Single End Lamps for Series Operation




Области применения

- Airfield Lighting

CBP_09.00 Product features and benefits, all [calc.]

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



Product family datasheet

Technical data

| Product description | General Product Information | | Electrical Data Nominal wattage | Lifetime Data Average Rated Life [GMS] |
|---------------------|-----------------------------|-------|------------------------------------|--|
| | ANSI code | LIF | | |
| 64322 | EXL | - | 30 W | 1500 hr |
| 64311 | - | J1/59 | 36 W | 1500 hr |
| 64321 | - | J1/57 | 45 W | 1500 hr |
| 64320 | EXM | - | 45 W | 1500 hr |
| 64346 | - | J1/58 | 100 W | 1200 hr |
| 64386 | - | J1/39 | 200 W | 1500 hr |
| 64350 | EVV | - | 110 W | 1000 hr |
| 58750 | EZL | - | 200 W | 1300 hr |
| 64354 | EWR | - | 150 W | 1500 hr |

Product family datasheet

Советы по безопасности

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.