

Lok-it! Power Series (PS)



Области применения

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

CBP_09.00 Product features and benefits, all [calc.]

- Compact design and short arc gap allows for smaller and brighter fixtures
- Fast lamp replacement with one-touch rotate and lock base and socket design
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Power series offers enhanced performance features and versatility, including BRILLIANT lamps with high CRI and BLUE lamps that offer 7500K for bright white light



 CONTAINS
MERCURY

Product family datasheet

Technical data

| Product description | Electrical Data | | Photometric Data | |
|---------------------------|-----------------|-----------------|-----------------------|-------------------|
| | Nominal wattage | Nominal voltage | Nominal luminous flux | Color temperature |
| Lok-it! 1000/PS | 1000 W | 85 V | 85000 lm | 6000 K |
| Lok-it! 1000/PS Brilliant | 1000 W | 85 V | 82000 lm | 6000 K |
| Lok-it! 1400/PS Brilliant | 1400 W | 95.5 V | 118000 lm | 6000 K |
| Lok-it! 1700/PS | 1700 W | 84.5 V | 135000 lm | 6000 K |
| Lok-it! 1800/PS Brilliant | 1800 W | 88 V | 148000 lm | 6000 K |
| Lok-it! 2000/PS Brilliant | 2000 W | 108 V | 165000 lm | 6000 K |

| Product description | Lifetime Data | |
|---------------------------|-----------------------------|--|
| | Average Rated Life [GMS] | |
| Lok-it! 1000/PS | 950 hr | |
| Lok-it! 1000/PS Brilliant | 750 hr | |
| Lok-it! 1400/PS Brilliant | 750 hr | |
| Lok-it! 1700/PS | 750 hr | |
| Lok-it! 1800/PS Brilliant | 750 hr | |
| Lok-it! 2000/PS Brilliant | 750 hr | |

Product family datasheet

Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.