

## HTI Single End



### Области применения

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

### CBP\_09.00 Product features and benefits, all [calc.]

- High luminance
- High luminous efficacy and efficiency



Product family datasheet

Technical data

Product description	Electrical Data			Photometric Data
	Nominal wattage [calc.]	Nominal voltage [calc.]	Nominal current [calc.]	Nominal luminous flux [calc.]
HTI 403 W/SE-Z	403 W	55 V	7.3 A	29000 lm

Product description	Lifetime Data
	Average Rated Life [GMS]
HTI 403 W/SE-Z	500 hr

## Product family datasheet

---

### Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.