

XBO \leq 450 W Double End



Области применения

- Endoscopy
- Microscopy
- Surgical Headlamps
- Fiber Illumination
- Solar Simulation
- Imaging & Scanning

CBP_09.00 Product features and benefits, all [calc.]

- High luminance / radiance with intense point source
- Broad, continuous spectral distribution
- High color rendering > 95
- High arc stability
- DC operation





XBO XENON SHORT ARC LAMPS



XBO XENON SHORT ARC LAMPS



XBO XENON SHORT ARC LAMPS

Product family datasheet

Technical data

Product description	Electrical Data			
	Nominal wattage	Lamp voltage	Lamp current	Type of current
XBO 75 W/2	75 W	12...16 V ³⁾	4.9...5.9 A	DC
XBO 75 W/2 OFR ¹⁾	75 W	12...16 V ³⁾	4.9...5.9 A	DC
XBO 100 W OFR ¹⁾	100 W	12.8...14.4 V ³⁾	7.0...7.4 A	DC
XBO 150 W/4 ²⁾	150 W	17...21 V ³⁾	7.5 A	DC
XBO 150 W/1	150 W	17...21 V ³⁾	7.5 A	DC
XBO 150 W/CR OFR ¹⁾	150 W	15...18 V ³⁾	8.5 A	DC

Product description	Operating Conditions			
	Cooling			
XBO 75 W/2	Convection			
XBO 75 W/2 OFR ¹⁾	Convection			
XBO 100 W OFR ¹⁾	Convection			
XBO 150 W/4 ²⁾	Forced			
XBO 150 W/1	Forced			
XBO 150 W/CR OFR ¹⁾	Forced			

¹⁾ OFR = Ozone-free version

²⁾ Lamp uses a special quality of quartz glass, known as SUPRASIL, which – in comparison to conventional quartz – provides higher transmission below 250 nm

³⁾ Initial voltage range

Product family datasheet

Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.