

HBO Microlithography Lamps for Süss Systems




Области применения

- Microlithography


CBP_09.00 Product features and benefits, all [calc.]

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Designed for long lasting performance
- Qualified with Süss



(Hg) CONTAINS MERCURY

Product family datasheet



HBO 5000W/S

Product family datasheet

Technical data

Product description	Electrical Data		Photometric Data	Physical Attributes & Dimensions
	Nominal wattage	Nominal voltage		
HBO 350 W/S	350 W	68 V	52.5 mm ²⁾	127.0 mm
HBO 1000 W/D	1000 W	37.7 V	89.5 mm ²⁾	240.0 mm
HBO 1000W/DHL	1000 W	45 V	89.5 mm	206.0 mm
HBO 5000 W/S ¹⁾	5000 W	50 V	143.5 mm ₂₎	360.0 mm

¹⁾ Lamp contains overpressure even in cold status - additional safety regulations, supplied with the lamps, have to be fulfilled. Please read Technical bulletin DO-SEM TB 004 carefully

²⁾ Distance from end of base to tip of anode or cathode (cold)

Product family datasheet

Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.