


LEDDriving PREMIUM SL P27/7W

Ideal replacement for any vehicle



Wide range of different light colors

Available in Cool White, Amber and Red for a variety of customization options



Excellent homogeneity

Non-selective illumination thanks to modern diffuser material



Matches P27/7W lamps

Upgrade to LED with simple plug & play replacement



Suitable LED replacement for P27/7W

The LEDDriving PREMIUM P27/7W retrofit lamps offer the perfect replacement for conventional P27/7W lamps. The lamps provide a modern and intense light with up to 6,000 Kelvin and are available in three different light colors: Cool White, Red and Amber. OSRAM offers a 5 year guarantee for these LEDDriving PREMIUM lamps. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Technical data

| Product description | Electrical Data | | | | | Photometric Data |
|--|-----------------|-------------------------|-------------------------|-------------------------|--------------|-------------------------------|
| | Power input | Nominal voltage [calc.] | Nominal wattage [calc.] | Power input tolerance | Test voltage | Nominal luminous flux [calc.] |
| LEDriving PREMIUM SL \triangleq P27/7W | 2.20 W | 12 V | 2 W | $\pm 10\%$ | 13.5 V | 200/26 lm |
| LEDriving PREMIUM SL \triangleq P27/7W | 2.20 W | 12 V | 2 W | $\pm 10\%$ / $\pm 10\%$ | 13.5 V | 39/5 lm |
| LEDriving PREMIUM SL \triangleq P27/7W | 2.20 W | 12 V | 2 W | $\pm 10\%$ | 13.5 V | 83/6.6 lm |







| Product description | Physical Attributes & Dimensions | | | Lifetime Data |
|--|----------------------------------|----------------|------------------|---------------|
| | Lamp base | Length [calc.] | Diameter [calc.] | Lifespan B3 |
| LEDriving PREMIUM SL \triangleq P27/7W | W2.5x16q | 49.0 mm | 25.7 mm | 2500 hr |
| LEDriving PREMIUM SL \triangleq P27/7W | W2.5x16q | 49.0 mm | 25.7 mm | 2500 hr |
| LEDriving PREMIUM SL \triangleq P27/7W | W2.5x16q | 49.0 mm | 25.7 mm | 2500 hr |

| Product description | Lifespan Tc | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
|--|-------------|---|----------------------------|------------------------|
| | | Primary Article Identifier | Candidate List Substance 1 | CAS No. of substance 1 |
| LEDriving PREMIUM SL \triangleq P27/7W | 5000 hr | 4052899434882 4052899434929 4052899434905 4052899321823 | Lead | 7439-92-1 |
| LEDriving PREMIUM SL \triangleq P27/7W | 5000 hr | 4052899435049 4052899321847 4052899435025 4052899435001 | Lead | 7439-92-1 |
| LEDriving PREMIUM SL \triangleq P27/7W | 5000 hr | 4052899434981 4052899321908 4052899434967 4052899434943 | Lead | 7439-92-1 |

Product family datasheet

| Product description | Safe Use Instruction | Declaration No. in SCIP database |
|--------------------------------|--|--|
| LEDDriving PREMIUM SL ≙ P27/7W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 28db75b7-fd3b-422f-a5de-2dcf2e7c4ad6 d2ab403c-fdb3-4f87-8b88-2b3331f5588b 6f5d42d5-5d26-4edf-a794-e48b54695207 e737b764-578a-4d7d-add2-30b2edb14643 7ee1a73b-ed38-4813-9e4a-af97150c3c51 |
| LEDDriving PREMIUM SL ≙ P27/7W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 0a407a8e-1046-4b83-b5fd-b44c926ee629 abe7748e-1e9b-4d45-ac5e-5449433a1c40 1e47812b-f9d1-428a-8313-1af975905eae 472a8638-e336-4a2b-b033-166ec18c606c |
| LEDDriving PREMIUM SL ≙ P27/7W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | bd7f697f-1c48-47c5-b587-313325c538c0 b7a1159c-cc1b-464d-ae2a-bb7047bd9c5d 1b90d07c-1493-4719-8bdc-d5a1cd5f612d 4eed9d52-7bf4-46c0-a2ed-bd66643d6ec6 |

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDiving Retrofits - Exchange overview (EN) |
|  | Brochures Sales Folder LEDiving replacement lamps (EN) |
|  | ref_pim_amsproduct360degreeimages LEDiving PREMIUM SL P27/7W 3557CW COOL WHITE |
|  | ref_pim_amsproduct360degreeimages LEDiving PREMIUM SL P27/7W 3557YE YELLOW |
|  | ref_pim_amsproduct360degreeimages LEDiving PREMIUM SL P27/7W 3557R RED |

Соответствие стандартам

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Ссылки

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

