

## LEDDriving PREMIUM SL W21/5W

Ideal replacement for any vehicle



### Wide range of different light colors

Available in Cool White, Amber and Red for a variety of customization options




### Excellent brightness

Thanks to advanced thermal management and superior light distribution



### Matches W21/5W lamps

Upgrade to LED with simple plug & play replacement



### Suitable LED replacement for W21/5W

The LEDDriving PREMIUM W21/5W retrofit lamps offer a suitable replacement for conventional W21/5W lamp bases. With these lamps, you have an easy plug & play replacement, regardless of base polarity. Thanks to homogenous light distribution a non-selective illumination is possible. For these LEDDriving PREMIUM lamps, OSRAM offers a 5 year guarantee. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage [calc.]	Nominal wattage [calc.]	Power input tolerance	Test voltage	Nominal luminous flux [calc.]
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.65 / 0.55 W	12 V	3 W	$\pm 10\%$	13.5 V	190/26 lm
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.54 / 0.44 W	12 V	1 W	$\pm 10\%$	13.5 V	35/5 lm
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.54 / 0.44 W	12 V	1 W	$\pm 10\%$	13.5 V	77/7 lm
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.65 / 0.55 W	12 V	1 W		13.5 V	190/26 lm
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.54 / 0.44 W	12 V	1 W		13.5 V	77/7 lm
LEDiving PREMIUM SL $\triangleq$ W21/5W	1.54 / 0.44 W	12 V	1 W		13.5 V	35/5 lm

Product description	Physical Attributes & Dimensions			Lifetime Data
	Lamp base	Length [calc.]	Diameter [calc.]	Lifespan B3
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	47.5 mm	20.0 mm	2500 hr
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	47.5 mm	20.0 mm	2500 hr
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	47.5 mm	20.0 mm	2500 hr
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	44.0 mm	19.4 mm	2500 hr
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	44.0 mm	19.4 mm	2500 hr
LEDiving PREMIUM SL $\triangleq$ W21/5W	W3x16q	44.0 mm	19.4 mm	2500 hr

Product description	Lifespan Tc	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)		
		Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899359550   4052899442535   4052899330788   4052899442511	Lead	7439-92-1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899330825   4052899442597   4052899442610	Lead	7439-92-1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899442573   4052899330849   4052899359598   4052899442559	Lead	7439-92-1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899427686   4052899513884   4052899513860   4052899427358   4052899513907	Lead	7439-92-1







Product family datasheet

		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Lifespan Tc	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899513969   4052899513945   4052899427730	Lead	7439-92-1
LEDiving PREMIUM SL $\triangleq$ W21/5W	5000 hr	4052899514065   4052899514041   4052899427785   4052899514027   4052899427457	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDiving PREMIUM SL $\triangleq$ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d721e103-1f61-44f6- 9bcd-92416a0189b4   e4547806-41fe- 417f-b839- 5e311e3e8e33   fd6ecf81-327b-4804- bfbb-e72e8a2348b9   2b371a39-7691- 4bd0-bf6c- 5781eac10de
LEDiving PREMIUM SL $\triangleq$ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a7f960b2-03e3- 44b7-ac32- e8d5deb1e26f   e9ee8b1f-e9c8-4956- 881b-e1e0ac3fab91   23c3b47b-2d1e- 4b23-8713- 1bb251211440   530688bd-369d- 402b-a921- f5bff11bab6e
LEDiving PREMIUM SL $\triangleq$ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	85d073d1-a247- 4921-be5f- b24372ea41be   4c31ba8a-9002- 4dd8-93c3- a440d6a46b30   2cdab345-f072-4aa3- b40a-353dcad2b086   9cbe2dd2-3ba3- 46da-ac32- f5df35f34af1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDiving PREMIUM SL ≙ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a8874f2d-0b08-4d95-9e4b-947dd4f3cd46   d0d85904-f138-426f-8349-6702394fe6c9   a24a50f7-ed29-4443-8742-c933e08a0646   537cc086-6a4a-4022-919c-bff80ebbc456   341b7c62-dd8d-43d0-b194-64272c137b3d   a1c6f226-5d34-4f3d-9463-241ba7414e4d   c0a70975-f5c3-40b1-a335-c4a79082674d
LEDiving PREMIUM SL ≙ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	44182716-e28d-404a-8a37-eb9b5f96a0d9   fa2f22a4-03c9-4cb8-8913-057737a22e06   ffbcf6a2-3e1b-4650-aacf-5438da80985c   bf453968-3e63-40d6-8eea-11904f3c757a   f769ad7d-aa0b-47d3-a33c-9574001c2493
LEDiving PREMIUM SL ≙ W21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6a726ed9-9687-470a-82f7-227a060d1fdc   4a5df613-434a-4819-894a-02f3f2a038ac   6eccc7a4-7b1a-4193-b2d4-8ea19e296160   8aa9abb3-fb56-41c1-aaf8-3e4c8e101b3d   e3b69b3b-6bb8-40b8-a444-d0d1287b2fa2   c0e5b53c-b8ab-437c-a701-8adff573f308   e84dd8e5-e6b3-499c-8c66-98f8bf20470a

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDiving Retrofits - Exchange overview (EN)
	Brochures Sales Folder LEDiving replacement lamps (EN)
	ref_pim_amsproduct360degreeimages LEDiving PREMIUM Retrofit 7915CW
	ref_pim_amsproduct360degreeimages LEDiving PREMIUM Retrofit 7915YE
	ref_pim_amsproduct360degreeimages LEDiving PREMIUM SL W21/5W 7915R RED

Соответствие стандартам

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Ссылки

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

