

COOL BLUE BOOST

Hyper white light for LED look for off-road use



Hyper white light for stylish LED look

For fatigue-free and comfortable driving



Up to 5,500 K¹⁾

High contrast and most stylish look



Enhanced brightness

More light allows to see farther and therefore react sooner



Hyper white light with up to 5,500 K for off-road use*

COOL BLUE BOOST features hyper white halogen light for LED look and high color temperatures of up to 5,500 K. The lamps generate enhanced brightness. These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

1) Measured in headlamps.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data	
	Power input	Nominal voltage [calc.]	Nominal wattage [calc.]	Test voltage	Nominal luminous flux [calc.]	
COOL BLUE BOOST $\triangleq$ H1	80 W ¹⁾	12 V	80 W	13.2 V	1150 lm	
COOL BLUE BOOST $\triangleq$ H4	75 / 68 W ¹⁾	12 V	100/90 W	13.2 V	1600/760 lm	
COOL BLUE BOOST $\triangleq$ H7	73 W ¹⁾	12 V	80 W	13.2 V	1000 lm	
COOL BLUE BOOST $\triangleq$ H11	75 W ¹⁾	12 V	75 W	13.2 V	1000 lm	
COOL BLUE BOOST $\triangleq$ H9	73 W ¹⁾	12 V	75 W	13.2 V	2100 lm	
COOL BLUE BOOST $\triangleq$ HB4	80 W ¹⁾	12 V	60 W	13.2 V		

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter [calc.]	Lifespan B3	Lifespan Tc	ECE category	Primary Article Identifier
COOL BLUE BOOST $\triangleq$ H1	$\pm 15\%$	8.5 mm	200 hr	400 hr	-	4052899436695 4052899439764 4052899437678 4062172388047
COOL BLUE BOOST $\triangleq$ H4	$\pm 15\%$ / $\pm 15\%$	17.0 mm	100 / 200 hr	200 / 400 hr	-	4062172388207 4052899436671 4052899439023 4052899437654 4052899439788
COOL BLUE BOOST $\triangleq$ H7	$\pm 15\%$	10.7 mm	200 hr	400 hr	-	4052899437371 4052899437692 4062172388221 4052899439047 4052899437333 4052899439801
COOL BLUE BOOST $\triangleq$ H11	$\pm 15\%$	12.0 mm	200 hr	400 hr	-	4052899437715 4052899439085 4052899439849 4052899437395 4052899437357 4062172388245
COOL BLUE BOOST $\triangleq$ H9	$\pm 10\%$	12.0 mm	250 hr	500 hr	-	4052899437418 4052899437739 4052899439863 4052899439108
COOL BLUE BOOST $\triangleq$ HB4		12.0 mm			-	4052899437548 4052899456846 4052899439146 4052899437777 4052899439900

Product family datasheet

Product description	Candidate List Substance 1	Declaration No. in SCIP database
COOL BLUE BOOST $\triangleq$ H1	No declarable substances contained	No declarable substances contained
COOL BLUE BOOST $\triangleq$ H4	No declarable substances contained	No declarable substances contained
COOL BLUE BOOST $\triangleq$ H7	No declarable substances contained	No declarable substances contained
COOL BLUE BOOST $\triangleq$ H11	No declarable substances contained	No declarable substances contained
COOL BLUE BOOST $\triangleq$ H9	No declarable substances contained	No declarable substances contained
COOL BLUE BOOST $\triangleq$ HB4	No declarable substances contained	No declarable substances contained

1) Maximum

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Certificate overview OSRAM Argentina
	Brochures Flyer Cool Blue Boost Jeep Version (EN)
	Brochures Flyer Cool Blue Boost (EN)
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST H1 62150CBB
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST H4 62193CBB
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST H7 62210CBB
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST H11 62211CBB
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST H9 62213CBB
	ref_pim_amsproduct360degreeimages COOL BLUE BOOST HB4/HB4A 69006CBB

Соответствие стандартам

*These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

