

## LEDDriving SL P13W

Ideal replacement for any vehicle



### High color temperatures of up to 6,000 K

Faster signals provide more reaction time for drivers behind you



### High brightness

Faster signals provide more reaction time for drivers behind you



### Replaces conventional P13W lamps

Upgrade to LED with simple plug & play replacement



### Suitable LED replacement for P13W

These LEDDriving SL retrofit lamps were specially developed for a suitable replacement of conventional P13W lamp types. Perfect for a multitude of applications, OSRAM LEDDriving SL illuminate vehicle exteriors with high color temperatures of up to 6,000 K. Thanks to their homogeneous light distribution, illumination is non-selective. OSRAM LED retrofits come with easy plug-and-play replacement, long life spans, low energy consumption – and 100% more style. OSRAM provides a 4-year guarantee for this product. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet






Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage [calc.]	Nominal wattage [calc.]	Test voltage	Nominal luminous flux [calc.]
LEDiving SL $\triangleq$ P13W	1.98 W	12 V	1 W	13.5 V	130 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter [calc.]	Lifespan B3	Lifespan Tc	Primary Article Identifier
LEDiving SL $\triangleq$ P13W	$\pm 15\%$	23.0 mm	1500 hr	4000 hr	4062172035866   4062172151764

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDiving SL $\triangleq$ P13W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0738803d-015c-49be-b2e7-0efc4c29c5f5   1d92d36d-ab69-4981-8cfc-99bd8a2282e0

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)
	Brochures Catalog LEDriving Premium SL und SL (EN)
	Brochures Sales Folder LEDriving replacement lamps (EN)
	ref_pim_amsproduct360degreeimages LEDriving SL P13W 828DWP

Соответствие стандартам

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

