

Данные о продуктовой линейке

TYREinflate 400



3.5 minutes inflation time¹⁾

Quick inflation, less time spent on maintenance, giving you more time to do other things



Wind-Up Power Cable

For quick and convenient storage



Bright directional white LED light

To assist in low light conditions



Digital Tyre Inflator

The OSRAM OTI400 can inflate a tyre from flat in 3.5 minutes¹⁾. With such a quick inflation time, less time is spent on tyre maintenance. It includes a backlit digital display and white LED light for maximum illumination in darkness. The OTI400's flat design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster. Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.

Данные о продуктовой линейке

Technical data

	Электрические параметры	Дополнительные данные	Возможности / мощности	Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Описание продукта	Номинальное напряжение	Тип дисплея	Предохранитель	Список компонентов вещества 1
TYRE inflate 400	11.1 V	Digital	10 A	Lead

Описание продукта	CAS-номер вещества 1	Инструкция по безопасному использованию	Номер декларации в базе данных SCIP
TYRE inflate 400	7439-92-1	Идентификация вещества из списка компонентов достаточна для безопасного использования изделия.	c35dce4c-772c-406f-ad5c-cb2f644cd972

Данные о продуктовой линейке

Загрузка данных

Файл



Brochures

TYREinflate 400

Соответствие стандартам

- 1) Based on inflating a 13" tyre from flat to 2.4 BAR
- 2) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.