

Данные о продуктовой линейке

LEDguardian TRUCK FLARE Signal TA19 Essential

LEDguardian TRUCK FLARE Signal TA19 Essential




Street legal

Street legal according to §53a StVZO. Use is also permitted in other EU countries¹⁾



Versatile applications

Mandatory in Germany for vehicles $\geq 3.5t$ and for vehicles $< 3.5t$ optional and recommended also in other countries



Robust and reliable

Water, dust and shock resistant



Ready for use immediately after purchase

Batteries included in scope of delivery



Light is safety – See and be seen with OSRAM

Our powerful LEDguardian TRUCK FLARE Signal TA19 Essential offers improved visibility and therefore increased safety for you and other road users. With 3 high-performance, long-life LEDs and a bright orange flashing light you can draw attention to yourself by day and night, and preventively alert other road users about a dangerous situation. The warning light is street legal and mandatory in Germany for vehicles $\geq 3.5t$ according to §53a TA19 StVZO, but it can also be used in other countries and for various vehicle types.¹⁾ Its compact design allows for convenient storage within easy reach in your vehicle. Thanks to its fold-out, robust feet, it can be quickly and easily set up next to the warning triangle. In addition, the rubberized standing feet provide non-slip stability, even in wind force 9. With an operating time of over 15 hours, the LEDguardian TRUCK FLARE Signal TA19 Essential offers long-lasting performance. The integrated test function allows you to check the battery capacity at any time. It is CE and GGVs/ADR certified²⁾, ensuring it meets the safety standards.

With an IP54 and IK06 protection rating, the LED warning light is resistant to the ingress of water and dust as well as insensitive to impacts and shocks. The package includes 4 x AA batteries, making the warning light ready for use immediately after purchase. Additionally, OSRAM provides a 2-year guarantee³⁾ on this product.

Данные о продуктовой линейке

Technical data

	Информация о продукте	Общая информация о продукте	Электрические параметры	
Описание продукта	Применение (категория и специфика)	Номер заказа	Номинальная мощность	Номинальное напряжение
LEDguardian TA19 Essential	Warning and safety lights	LEDsL106	3 W	6.0 V

	Фотометрические данные		Физические характеристики и размеры	
Описание продукта	Цветовая температура	Цветность светодиода	Вес продукта	Длина
LEDguardian TA19 Essential	2000 K	оранжевый	566.00 g	237.0 mm

			Срок службы	Дополнительные данные
Описание продукта	Ширина	Высота	Гарантия	Тип батареи
LEDguardian TA19 Essential	91.0 mm	43.0 mm	2 years	Alkaline

	Возможности / мощности	Сертификаты и Стандарты	Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Описание продукта	Технология	IK Class	Список компонентов вещества 1	CAS-номер вещества 1
LEDguardian TA19 Essential	LED	IK06	Lead	7439-92-1

Описание продукта	Инструкция по безопасному использованию	Номер декларации в базе данных SCIP
LEDguardian TA19 Essential	Идентификация вещества из списка компонентов достаточно для безопасного использования изделия.	2dfb9ae0-4f69-449a-8593-c11395032197

Данные о продуктовой линейке

Загрузка данных

Файл	
	User instruction GPRS_Инструкции по символам безопасности
	User instruction LEDguardian TRUCK FLARE Signal TA19 ESSENTIAL

Соответствие стандартам

1) Use is also permitted in other EU countries, provided that the respective national regulations are complied with2) Approved in dangerous goods transports according to European Agreement concerning the International Carriage of Dangerous Goods by Road & Dangerous Goods Regulation Road3) For precise conditions please refer to: www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user manual.

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.