

LEDDriving SL P27/7W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P27/7W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDDriving SL P27/7W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Electrical Data | | | | | Photometric Data |
|---------------------------------|-----------------|-----------------|-----------------|-----------------------|--------------|-----------------------|
| | Power input | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Nominal luminous flux |
| LEDiving SL \triangleq P27/7W | 2.50 W | 12 V | 1 W | $\pm 25\%$ | 13.5 V | 145/30 lm |

| Product description | Physical Attributes & Dimensions | | | Lifetime Data |
|---------------------------------|----------------------------------|---------|----------|---------------|
| | Lamp base | Length | Diameter | Lifespan B3 |
| LEDiving SL \triangleq P27/7W | W2.5x16q | 49.0 mm | 25.7 mm | 1500 hr |

| Product description | Lifespan Tc | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
|---------------------------------|-------------|---|----------------------------|------------------------|
| | | Primary article identifier | Candidate list substance 1 | CAS No. of substance 1 |
| LEDiving SL \triangleq P27/7W | 4000 hr | 4062172151641 4062172401753 | Lead | 7439-92-1 |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|---------------------------------|--|--------------------------------------|
| LEDiving SL \triangleq P27/7W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 29e5e603-3b88-4f05-9f2b-944024bdbaa9 |

Product family datasheet

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.