

Product family datasheet

TYREinflate 450

**Rapid Inflation Time**

Inflate the tire to the desired pressure in ca. 3.5 minutes**

**Wind-up Cable**

Winding/unwinding mechanism for a neatly rolled up cable

**LED Light**

Easy to operate even in darkness and in low light conditions

**Rapid tyre inflator with wind-up cable**

The OSRAM Tyreinflate 450 can inflate a tyre from flat in 3.5 minutes**. Comes with auto stop feature to accurately get the desired pressure for your tyre. Includes a backlit digital display and white LED light for optimal illumination in darkness.

The Tyreinflate 450's flat, solid design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster. Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.

**based on inflating a 13" tyre from flat to 2.41 BAR

Product family datasheet

Technical data

	Electrical Data	Additional product data	Capabilities	Environmental & Regulatory Information
Product description	Nominal voltage	Display Type	Предохранитель	Candidate List Substance 1
TYRE inflate 450	11.1 V	Digital	10 A	Lead

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
TYRE inflate 450	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	dda41c6e-d521-4522-a227-e170d9cf4d66

Product family datasheet

Download Data

File
 User instruction TYREinflate 450
 Movie application Tyreinflate How to Video (RU)
 Product movie Tyreinflate 450 Product Video (EN)
 Product movie Tyreinflate 450 Product Video (RU)
 Product movie Tyreinflate How to Video (EN)
 Product movie Tyreinflate How to Video (IT)
 Product movie Tyreinflate 450 Product Video (ITA)
 Video OSRAM TYREinflate 450: Rapid tyre inflator with wind-up cable, LED light and digital display
 Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

Советы по безопасности

Product won't exceed noise levels of more than 90 dB

Соответствие стандартам

CE and EAC compliant

* for precise conditions please refer to: www.osram.com/am-guarantee

** based on inflating a 13" tyre from flat to 2.41 BARApplication advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.