

## HMI Single End Lamps (other)



### Области применения

- Studio, TV, & Film
- Stage & Theatre
- Professional & High Speed Photography
- Solar Simulation


### CBP\_09.00 Product features and benefits, all [calc.]

- High intensity light providing true color performance with a >90
- Longer life with heat dissipating round moly-foil design on lamps  $\geq 6000\text{W}$
- Mechanically robust with eXtreme Seal (XS) technology, up to  $450^\circ\text{C}$  at the pinch seal
- Capable of hot restrike ignition
- High stability of color temperature over lifetime
- High energy efficiency providing up to  $100 \text{ lm/W}$



(Hg) CONTAINS MERCURY

## Product family datasheet



HMI 12000W/ SE

## Product family datasheet

### Technical data

Product description	Electrical Data			Photometric Data
	Nominal wattage	Nominal voltage	Nominal current	
HMI 2500 W/SE XS	2500 W	115 V	25.6 A	240000 lm
HMI 4000 W/SE XS	4000 W	200 V	24 A	380000 lm
HMI 12000 W/SE XS	12000 W	160 V	75 A	1150000 lm

Product description	Lifetime Data	
	Average Rated Life [GMS]	
HMI 2500 W/SE XS	500 hr	
HMI 4000 W/SE XS	500 hr	
HMI 12000 W/SE XS	500 hr	

## Product family datasheet

---

### Советы по безопасности

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.