

Product family datasheet

HBO ≤ 200W Double End



CBP_03.00 Areas of applicat, all [calc.]

- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Microscopy
- Solar Simulation

CBP_09.00 Product features and benefits, all [calc.]

- High luminance / radiance with intense point source
- Broad spectral distribution in the visible and ultraviolet range
- Enhanced UV characteristics available on some types
- High arc stability



(Hg) CONTAINS MERCURY

Product family datasheet

Technical data

Product description	Electrical Data			Lifetime Data Average Rated Life [GMS]
	Nominal wattage	Lamp voltage	Lamp current	
HBO 50 W/AC 39 V	50 W	39...45 V ¹⁾	1.1...1.3 A	100 hr
HBO 50 W/AC 34 V	50 W	34...39 V ¹⁾	1.3...1.5 A	100 hr
HBO 50 W/3	50 W	20...26 V ¹⁾	1.9...2.5 A	200 hr
HBO 100 W/2	100 W	17...25 V ¹⁾	4.3...5.6 A	200 hr
HBO 103 W/2	103 W	17...25 V ¹⁾	4.0...5.0 A	300 hr
HBO 200 W/2 57 V	200 W	57...65 V ¹⁾	3.0...3.5 A	400 hr
HBO 200 W/4	200 W	54...63 V ¹⁾	3.0...3.7 A	200 hr
HBO 200 W/DC TM	200 W	57...65 V ¹⁾	3.0...4.3 A	400 hr
HBO 202 W/4	202 W	57...65 V ¹⁾	3.6 A	200 hr
HBO 200 W/DC 57 V	200 W	48...65 V ¹⁾	3.0...4.3 A	1000 hr

¹⁾ Initial electrical values

Product family datasheet

CBP_05.00 Safety advice, all [calc.]

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.