

LEDinspect SLIM MAX1000

Inspectionlights



Dimmer Switch

Individually adjustable brightness levels with up to 1000 lm




1000 Lumen

Bright, white LED light and uniform light distribution



Multi-Angle Light Output

High flexibility due to individual adjustment of the light beam



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. Charging cable and mains adaptor are included in the scope of supply. In accordance with the IP protection class IP65,

this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product*

Product family datasheet

Technical data

	Product information	General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Order reference [calc.]	Nominal wattage [calc.]	Nominal voltage [calc.]
INSPECTION LAMP	LED inspection lights	LEDIL410	10 W	3.7 V
INSPECTION LAMP	LED inspection lights	LEDIL410	9 W	3.7 V

	Photometric Data			Physical Attributes & Dimensions
Product description	Color temperature [calc.]	Nominal luminous flux [calc.]	Light color LED	Length [calc.]
INSPECTION LAMP	6000 K	1000 lm	White	365.0 mm
INSPECTION LAMP	6000 K	1000 lm	White	365.0 mm

				LED module information
Product description	Width [calc.]	Height [calc.]	Product weight	Number of LEDs per module
INSPECTION LAMP	65.0 mm	50.0 mm	308.00 g	2
INSPECTION LAMP	50.0 mm	50.0 mm	340.00 g	2

	Colors & materials	Lifetime Data	Additional product data	
Product description	Base color	Guarantee	Number of included batteries	Scope of battery
INSPECTION LAMP	Black / Orange	2 years	1	Yes
INSPECTION LAMP	Black / Orange	2 years	1	Yes




		Capabilities	Certificates & standards	Logistical data
Product description	Type of Battery	Technology	IK Class	Watt hour per battery [GMS]
INSPECTION LAMP	Rechargeable	LED	IK06	10.00
INSPECTION LAMP	Rechargeable	LED	IK06	9.49

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
INSPECTION LAMP	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	92705a2c-f48c-4c87-b217-28738f7fa298

Product family datasheet

Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)				
Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
INSPECTION LAMP	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	99d5749d-0f33-4ebf-9ff7-b17da405d236

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	User instruction LEDinspect SLIM MAX 1000
	Movie application LEDinspect Inspection Lights Trailer

Соответствие стандартам

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.