


Данные о продуктовой линейке

LEDDriving™ HL EASY XEN D1S



Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



Compact LED replacement for conventional high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Данные о продуктовой линейке

Technical data

Описание продукта	Электрические параметры				Фотометрические данные
	Мощность на входе	Номинальное напряжение	Номинальная мощность	Тестовое напряжение	Световой поток
LEDiving HL EASY XEN ≙ D1S	40 W	12 V	40 W	13,2 V	5000 lm

Описание продукта	Допуск по отклонению светового потока	Физические характеристики и размеры	Срок службы	Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Диаметр	Срок службы Тс	Основной идентификатор изделия	Список компонентов вещества 1
LEDiving HL EASY XEN ≙ D1S	±25 %	13.8 mm	5000 hr	4062172421447	Не содержит веществ, подлежащих декларированию

Описание продукта	Номер декларации в базе данных SCIP
LEDiving HL EASY XEN ≙ D1S	Не содержит веществ, подлежащих декларированию

Данные о продуктовой линейке

Загрузка данных

Файл	
	User instruction GPRS_Инструкции по символам безопасности

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.

