

## LEDDriving HL EASY GEN 2 H8/H9/H11/H16



### Ultra compact LED replacement for conventional high and low beam lamps

"Socket Design" – no adapters and caps needed



### Easy plug & play installation

Allowing a high compatibility and an easy installation



### Cool White color temperature

Better visibility thanks to daylight effect



### LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

### Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDiving HL EASY $\triangleq$ H8/H11/H16	26 W	12 V	26 W	13.5 V	2000 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Diameter	Lifespan Tc	Primary Article Identifier	Declaration No. in SCIP database
LEDiving HL EASY $\triangleq$ H8/H11/H16	$\pm 25$ %	14.8 mm	1000 hr	4062172426527	In work

## Product family datasheet

### Download Data

File	
	User instruction GPRS_Safety symbols instructions

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

