

Данные о продуктовой линейке

LEDDriving HL EASY GEN 2 HB3/HIR1/H10/HB4/HIR2



Ultra compact LED replacement for conventional high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Данные о продуктовой линейке


Technical data

| Описание продукта | Электрические параметры | | | | Фотометрические данные |
|--|-------------------------|------------------------|----------------------|---------------------|------------------------|
| | Мощность на входе | Номинальное напряжение | Номинальная мощность | Тестовое напряжение | Световой поток |
| LEDiving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2 | 26 W | 12 V | 26 W | 13,2 V | 2000 lm |

| Описание продукта | Допуск по отклонению светового потока | Физические характеристики и размеры | Срок службы | Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|--|---------------------------------------|-------------------------------------|----------------|--|--|
| | | Диаметр | Срок службы Тс | Основной идентификатор изделия | Номер декларации в базе данных SCIP |
| LEDiving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2 | ±25 % | 14.8 mm | 1000 hr | 4062172426428 | В работе |

Данные о продуктовой линейке

Загрузка данных

| Файл | |
|---|--|
|  | User instruction GPRS_Инструкции по символам безопасности |

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.

