

TYREinflate 830

TYREinflate 830 OTI 830



Digital Auto Stop

Automatic stop function when the preset pressure is reached



Deflator Valve

For deflating too much air



Светодиодный фонарик

Easy to operate even in the dark and in reduced visibility conditions



Inflation Time

Can inflate a 13" tyre in approx. 2 minutes and a 15" tyre in approx. 5 minutes²⁾³⁾



Large Vehicle Digital Tyre Inflator


The OSRAM TYREinflate 830 has been specially developed for use with larger vehicles and their tyres, making it ideal for cars, caravans, motorhomes, off-road vehicles, minibuses and vans. This tyre inflator can inflate a 13" tyre in approx. 2 minutes and a 22" tyre in approx. 5 minutes²⁾3. The auto stop function and the deflator valve help to keep the tyres optimally inflated. This can also reduce the risk of over- or under-inflation and the resulting possible damage to the tyres. The TYREinflate 830 has a 4-metre power cable for the accessibility to all four tyres and plugs directly into your vehicle's 12-volt socket. The backlit LED display and integrated LED light provide improved readability of the pressure settings and improved illumination of the working area even in reduced visibility conditions or at night. Also included are three adapters for inflating sports balls and other small inflatables and a storage bag to protect the unit and store it neatly. OSRAM offers a 2-year guarantee¹⁾ on this product. 1) For precise conditions please refer to: www.osram.com/am-guarantee2) Based on inflating a 13" tyre from flat to 2.4 BAR /22" tyre from flat to 2.6 bar³⁾ Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Данные о продуктовой линейке

Technical data

	Информация о продукте					
Описание продукта	Дефлятор	Светодиодная подсветка	Предустановленные функции		Автоматическая остановка	
TYRE inflate 830	Да	Да	Да		Да	
		Электрические параметры	Размеры и вес			Дополнительные данные
Описание продукта	Чехол для хранения	Номинальное напряжение	Длина	Ширина	Высота	Тип дисплея
TYRE inflate 830	Да	120 В	2500 mm	1500 mm	1000 mm	Digital
		Возможности / мощности	Классификация		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Описание продукта	Дополнительно	Предохранитель	Номер заказа		Date of Declaration	
TYRE inflate 830	3 Piece Adaptor Kit	15 A	OTI830		07-03-2024	
Описание продукта	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1		Safe Use Instruction	
TYRE inflate 830	4062172294492	Lead	7439-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Описание продукта	Declaration No. in SCIP database					
TYRE inflate 830	370c6b6d-841b-4ec5-8420-c49baafca26b					

Загрузка данных

Файл	
	User instruction TYREinflate OTI830 Large Vehicle Digital Tyre Inflator 12V DC

Соответствие стандартам

1)For precise conditions please refer to: www.osram.com/am-guarantee2)Based on inflating a 13" tyre from flat to 2.4 BAR /22" tyre from flat to 2.6 bar3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice:For more detailed application information and graphics please see product datasheet and the user instruction.

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.