

Product family datasheet

## LEDriving HL INTENSE H4/H19



Up to +350% more brightness



Very compact LED replacement for conventional H4/H19 high and low beam lamps (2in1)



Cool White color temperature of 6,000 K



5-year OSRAM guarantee

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112

Reduced glaring thanks to an optimized light distribution

Better visibility thanks to daylight effect

For precise conditions, please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)



OSRAM's highest performing LED off-road retrofit lamp

With up to +350% more brightness (compared to ECE R112) and a very compact LED replacement of conventional H7/H18 and H4/H19 high and low beam lamps, the LEDriving HL INTENSE is OSRAM's highest performing LED off-road retrofit lamp ever! This LED retrofit lamp offers OSRAM top technology beam pattern as well as an easy installation with a wide OSRAM range of suitable accessories. Top thermal management technology with integrated active cooling – a high speed fan ensures maximized heat dissipation for more powerful

performances. Also premium OSRAM quality, manufactured in a certified OSRAM production plant in Italy, and a 5-year guarantee as well as a long service life. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

The LED high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a color temperature of 6,000K. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for an even wider range of car models. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

### Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	
LEDriving HL INTENSE $\triangleq$ H4/H19	25 / 21.0 W	12 V	27 W	13.2 V	1900/1350 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions		Lifetime Data	Environmental & Regulatory Information	
		Diameter	Lifespan Tc		Primary Article Identifier	Candidate List Substance 1
LEDriving HL INTENSE $\triangleq$ H4/H19	$\pm 20\%$	18.5 mm	5000 hr	4062172306454	Lead	

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDriving HL INTENSE $\triangleq$ H4/H19	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	00479b3c-8dd8-47ab-8d78-e578b9e2419f

# Product family datasheet

## Download Data

File
 User instruction LEDriving HL INTENSE
 User instruction GPRS_Safety symbols instructions
 Brochures LEDriving Retrofits - Exchange overview (EN)

## Соответствие стандартам

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Application advice

For more detailed application information and graphics please see product datasheet.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

