

LEDDriving HL EASY H15




Ultra compact LED replacement for conventional H15 high and low beam lamps (2in1)

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation for an even wider range of car models.



Cool White color temperature

Better visibility thanks to daylight effect

LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HL EASY retrofits provide an ultra-compact LED replacement of conventional H7/H18, H4/H19 and H15 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With



Product family datasheet

the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data



Product description	Electrical Data			Photometric Data		Physical Attributes & Dimensions
	Power input	Nominal voltage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter
LEDiving HL EASY \cong H15	16.5 / 3.8 W	12 V	13.2 V	1250/250 lm	\pm 25 %	15.8 mm

Product description	Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Lifespan Tc	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDiving HL EASY \cong H15	1000 hr	4062172294966 4062172398350 4062172312592	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDiving HL EASY \cong H15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	71c142ec-374e-4388-9e54-b12e0eaecde1 454fe0c4-a884-4b8c-9105-1bd9044203c9 ee9bec0d-db20-4643-8e67-aa9e301fc3a5

Product family datasheet

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

