

# LEDriving HLM EASY H4/H19



**Cool White color temperature of 6,000 K**

Better visibility thanks to daylight effect



**Superior brightness**

Allowing a high compatibility and an easy installation.



**LED replacement for conventional T19 high and low beam lamps**

Reduced glaring thanks to an optimal light distribution



**LED high and low beams lamps with plug & play system for motorcycles.**

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

### Technical data

| Product description    | Electrical Data |                 |                 | Photometric Data      |                         |
|------------------------|-----------------|-----------------|-----------------|-----------------------|-------------------------|
|                        | Power input     | Nominal voltage | Nominal wattage | Nominal luminous flux | Luminous flux tolerance |
| LEDriving HLM EASY T19 | 4.5 W / 5.5 W   | 13.5 V          | 5 W             | 600/500 lm            | ±15 %                   |

| Product description    | Physical Attributes & Dimensions |  | Lifetime Data |             | Environmental & Regulatory Information                                |                            |                            |
|------------------------|----------------------------------|--|---------------|-------------|---|----------------------------|----------------------------|
|                        | Diameter                         |  | Lifespan B3   | Lifespan Tc | Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | Primary Article Identifier | Candidate List Substance 1 |
| LEDriving HLM EASY T19 | 18.4 mm                          |  | 500 hr        | 1000 hr     | 4062172345545   406217239983  | Lead                       |                            |

| Product description    | CAS No. of substance 1 | Safe Use Instruction   | Declaration No. in SCIP database  |
|------------------------|------------------------|--|---|
| LEDriving HLM EASY T19 | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | efa593e8-2c11-4e97-9734-d514687a1b08   5ec6e727-7f8a-4bc0-ac15-c8ce50c92a5f |

# Product family datasheet

## Download Data

### File



User instruction  
GPRS\_Safety symbols instructions

### CBP\_0L.00 Legal advice, all [calc.]

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.