

Product family datasheet

LEDriving Universal Headlights



4 function Universal Headlight

Maximum flexibility and a wide range of possible applications



Brilliantly white light with up to 6500K

Exceptional illumination, performance, quality, shape, durability and functionality



IP & IK protection classes

Tested and validated in a DIN-certified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



2 years OSRAM guarantee¹⁾

Powerful performance and exceptionally long service life



Individual light for individual requirements

Experience maximum flexibility and a wide range of possible applications with the OSRAM LEDriving Universal Headlights. The Bi-LED modules seamlessly integrate both low beam and high beam functionalities into a single headlamp module, providing you with the option for additional position light and daytime running light functions based on your requirements. They are available for left-hand drive (LEDUHL101/LEDUHL103) and right-hand drive (LEDUHL102/LEDUHL104). The four headlights in total offer superior illumination, performance, and quality. They

are designed to deliver a brilliantly white light with exceptional clarity, ensuring enhanced visibility on the road. With their durable construction and sleek design, the headlights combine both style and functionality. The Universal Headlights are suitable for 12V and 24V vehicles and come in four different variants with a wide range of applications: the basic functions of low beam or high beam can be combined with other functions such as daytime running light and position light. Additionally, OSRAM has developed a specially designed mounting kit for easy, uncomplicated and flexible assembly. The LEDriving Mounting Kit MK1 comes with a mounting plate, screws, clips and inserts and offers three mounting options: direct mount, mount with a mounting plate, and optional mount with a leveling motor. This allows for easy adaptation to different vehicle types. When it comes to external influences, the Universal Headlights are built to withstand extreme conditions. They are resistant to water, dust, shocks, vibrations, and a wide range of temperatures (validated according to the highest IP & IK protection classes IP6K7 & IP6K9K). Trust in quality and performance – OSRAM LEDriving Universal Headlights are proudly made in Europe, meet the highest standards and have a 2-year OSRAM guarantee¹⁾.¹⁾For precise conditions refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

<table border="1"> <thead> <tr> <th colspan="2">Electrical Data</th><th colspan="2">Photometric Data</th><th>Environmental & Regulatory Information</th></tr> <tr> <th colspan="2"></th><th colspan="2"></th><th>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</th></tr> <tr> <th>Product description</th><th>Nominal voltage</th><th>Nominal wattage</th><th>Nominal luminous flux</th><th>Candidate List Substance 1</th></tr> </thead> <tbody> <tr> <td>LEDriving Universal Headlight 101-102</td><td>12/24 V</td><td>33 W</td><td>780-1180 lm</td><td>Lead</td></tr> <tr> <td>LEDriving Universal Headlight 103-104</td><td>12/24 V</td><td>28 W</td><td>780-1180 lm</td><td>Lead</td></tr> </tbody> </table>					Electrical Data		Photometric Data		Environmental & Regulatory Information					Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	Product description	Nominal voltage	Nominal wattage	Nominal luminous flux	Candidate List Substance 1	LEDriving Universal Headlight 101-102	12/24 V	33 W	780-1180 lm	Lead	LEDriving Universal Headlight 103-104	12/24 V	28 W	780-1180 lm	Lead
Electrical Data		Photometric Data		Environmental & Regulatory Information																									
				Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)																									
Product description	Nominal voltage	Nominal wattage	Nominal luminous flux	Candidate List Substance 1																									
LEDriving Universal Headlight 101-102	12/24 V	33 W	780-1180 lm	Lead																									
LEDriving Universal Headlight 103-104	12/24 V	28 W	780-1180 lm	Lead																									

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDriving Universal Headlight 101-102	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	51c804e5-a716-423b-9b00-79678aa88245 a268750e-65fc-4122-a409-e28a0f4e1b0b
LEDriving Universal Headlight 103-104	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6904f19b-82a9-4db3-b918-16301695a51d ae047939-c152-4b35-97cd-876f5b0b5933

Product family datasheet

Download Data

File
 User instruction LEDriving UNIVERSAL HEADLIGHT, LEDriving UNIVERSAL HEADLIGHT
 User instruction GPRS_Safety symbols instructions
 Movie application LEDriving Universal Headlights LEDUHL Produkt Video DE
 Movie application LEDriving Universal Headlights LEDUHL Product Video EN

Советы по безопасности

For detailed application information, please refer to the product data sheet and the user instruction

Соответствие стандартам

1)For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.