

Product family datasheet

LEDriving HL EASY H3



Ultra compact LED replacement for conventional H3 high and low beam lamps (2in1)

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation for an even wider range of car models.



Cool White color temperature

Better visibility thanks to daylight effect

LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDriving HL EASY retrofits provide an ultra-compact LED replacement of conventional H1, H3, H7/H18, H4/H19 and H15 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation. The LEDriving HL EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types.



Product family datasheet

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	
LEDriving HL EASY \triangleq H3	8 W	12 V	8 W	13.2 V	900 lm

Product description	Luminous flux tolerance	Diameter	Lifetime Data Lifespan Tc	Environmental & Regulatory Information	
				Physical Attributes & Dimensions	Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
LEDriving HL EASY \triangleq H3	$\pm 25\%$	12.5 mm	1000 hr	4062172369329 4062172398053 4062172367264	Lead

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDriving HL EASY \triangleq H3	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2c86b15b-e1ac-4eb7-91df-2ed36dd6a9dd 244d3c63-ded2-43df-9b50-31be8f569b7e 40378725-5108-442c-928d-edcb4ef4195f

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Соответствие стандартам

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

